

DESIGN OF COOLING CHANNEL IN HOT STAMPING TOOL BY HEURISTIC APPROACH

MOHD FAWZI BIN ZAMRI

Master

UNIVERSITI MALAYSIA PAHANG



SUPERVISOR'S DECLARATION

I hereby declare that I have checked this thesis and in my opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Master of Engineering in Manufacturing.

(Supervisor's Signature)

Full Name : ASSOC. PROF. DR AHMAD RAZLAN BIN YUSOFF

Position : SENIOR LECTURER

Date :



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

(Student's Signature)

Full Name : MOHD FAWZI BIN ZAMRI

ID Number : MMF13002

Date :

DESIGN OF COOLING CHANNEL IN HOT STAMPING TOOL BY HEURISTIC
APPROACH

MOHD FAWZI BIN ZAMRI

Thesis submitted in fulfillment of the requirements
for the award of the degree of
Master of Engineering (Manufacturing)

Faculty of Manufacturing Engineering
UNIVERSITI MALAYSIA PAHANG

2017

ACKNOWLEDGEMENTS

First of all, thanks to Allah the Almighty for giving me the strength to complete my project successfully. I would like to express my sincere gratitude to my supervisor Assoc. Prof Madya Dr Ahmad Razlan Yusoff for his ideas, invaluable guidance, continuous encouragement and constant support in making this project possible. My deep thanks go to my dearest family, especially to my father Zamri Bin Marzuki and mother, Fauziah Binti Masri, who are always support and pray for my success throughout this project. Their support provides me the spirit and strength that I require to endure throughout the period of my study. I would like to thank the lecturers and technicians at Faculty of Manufacturing Engineering and other related faculties for their valuable comments and constructive criticisms. Besides that, I would like to thank to UMP, this work were funded by Internal Grant, RDU 130343 Development of Hot Stamping Die for Ultra High Strength Steels in Automotive Component Application and Postgrad Research Scheme (PGRS). Finally, I would also like to thank my fellow colleagues for being there for me through thick and thin.

ABSTRAK

Disebabkan permintaan untuk mengurangkan pelepasan gas, penjimatan tenaga, dan pengeluaran kenderaan yang lebih selamat, pembangunan bahan ultra kekuatan tinggi keluli (UHSS) adalah bukan perkara yang remeh. Untuk mengukuhkan bahan UHSS seperti keluli boron, ia diperlukan untuk menjalani beberapa proses iaitu pemanasan melalui cap panas pada suhu dan masa tertentu serta penyejukan melalui pelindapkejutan. Dalam proses cap panas, die yang sama digunakan seperti dalam proses cap sejuk, tetapi dengan saluran penyejukan tambahan. sistem saluran penyejukan disepadukan ke dalam reka bentuk die untuk mengawal kadar pemindahan haba untuk proses kosong panas pelindapkejutan. Semasa proses pelindapkejutan, reka bentuk mati berkesan menyumbang ke arah pencapaian kadar pemindahan haba yang optimum dan pengedaran suhu homogen pada kekosongan panas. Dalam kajian ini, parameter reka bentuk saluran penyejukan iaitu garis pusat saluran pendinginan (CA), padang antara saluran penyejukan (CB), jarak saluran penyejukan ke permukaan alat (CC), dan jarak saluran penyejuk ke alat dinding (CD) dioptimumkan untuk alat rata dan U-bentuk menggunakan kaedah heuristik. Kaedah heuristik digabungkan dengan analisis haba dan statik analisis unsur terhingga (FEA) melalui ANSYS untuk menentukan reka bentuk optimum penyejukan penyejukan panas. Analisis statik dilakukan untuk memastikan alat tersebut mampu menahan tekanan yang dikenakan, sementara analisis haba dilakukan untuk memastikan pengedaran suhu homogen. Setiap parameter saluran penyejukan dioptimumkan dan ditanda aras dengan kaedah tradisional Taguchi. Kemudian, percubaan proses cap panas dilakukan untuk mendapatkan pengedaran suhu produk dan alat kosong. Seterusnya, hasil simulasi dibandingkan dengan kerja eksperimen untuk tujuan pengesahan. Hasil pengedaran suhu antara FEA dan eksperimen adalah mendapatkan ralat kurang daripada 20 %. Reka bentuk optimum alat setem panas dengan pemindahan haba yang tinggi dan tegasan von Mises yang lebih rendah (VMS), parameter berikut (sebelum ini ditakrifkan sebagai CA, CB, CC, CD mm) diperlukan (8,8,10) mm untuk alat rata, (8,8,8,10) mm untuk alat U-bentuk atas dan (8,8,8,8) mm untuk alat U-bentuk yang lebih rendah. Juga jelas bahawa corak pengedaran suhu model FEA bersetuju dengan keputusan percubaan. Berdasarkan alat bentuk rata, ralat peratusan purata untuk taburan haba kosong ialah 1.83 % dan untuk alat itu ialah 2.67%. Bagi alat U-shape, ralat peratusan purata bagi alat atas, alat bawah dan pengagihan haba kosong masing-masing 16.65 % 17.95 % dan 7.92 %. Kekuatan tegangan dan nilai kekerasan produk kosong (sampel rata dan U berbentuk) diukur menjadi kira-kira 1200 MPa dan 600 HV, masing-masing. Kesimpulannya, berdasarkan parameter yang dioptimumkan dalam kajian ini, jelaslah kekuatan tegangan yang tinggi dengan nilai kekerasan yang tinggi dapat dihasilkan dari kaedah heuristik.

ABSTRACT

Owing to the demand for reducing gas emissions, energy savings, and the production of safer vehicles, the development of Ultra High Strength Steel (UHSS) materials is non-trivial. To strengthen a UHSS material such as boron steel, it is required to undergo a number of processes namely, heating it via hot stamping at a certain temperature and time as well as cooling it through quenching. In the hot stamping process, a similar die is used as in the cold stamping process, but with additional cooling channels. The cooling channel systems are integrated into the die design to control the heat transfer rate for quenching process of hot blanks. During quenching process, an effective die design contributes towards the achievement of the optimum heat transfer rate and homogeneous temperature distribution on hot blanks. In this study, the parameters of the cooling channel design i.e. the diameter of cooling channel (C_A), the pitch between cooling channel (C_B), the cooling channel distance to tool surface (C_C), and the cooling channel distance to wall tool (C_D) are optimised for a flat and U-shape tool using heuristic method. The heuristic method is coupled with the thermal and static analysis of finite element analysis (FEA) via ANSYS to determine the optimum design of hot stamping cooling channels. The static analysis are performed to ensure that the tool is able to withstand the applied pressure, whilst the thermal analysis was carried out to ensure homogeneous temperature distribution. Each parameter of the cooling channels optimised and benchmarked with traditional Taguchi method. Then, hot stamping process experiment is conducted to get the temperature distribution of the blank product and tool. Next, the simulation results were compared with experimental works for validation purpose. The result of the temperature distribution between FEA and experiment expected error less than 20 %. It is found that the optimum design of the hot stamping tool with a high heat transfer and lower von Mises stress (VMS), the following parameters (previously defined as C_A , C_B , C_C , C_D in mm) are required (8,8,10) mm for the flat tool, (8,8,8,10) mm for the upper U-shape tool and (8,8,8,8) mm for the lower U-shape tool, respectively. It is also evident that the pattern of the temperature distribution of the FEA model agrees the experimental results. Based on the flat shape tool, the average percentage error for the blank heat distribution is 1.83 % and for the tool is 2.67 %. As for the U-shape tool, the average percentage error for the upper tool, lower tool, and the blank heat distribution are 16.65 % 17.95 % and 7.92 %, respectively. The tensile strength and the hardness value of the blank products (flat and U-shaped samples) are measured to be approximately 1200 MPa and 600 HV, respectively. In conclusion, based on the aforementioned optimised parameters in the study, it is apparent that a high tensile strength with high value of hardness product could be produced from the heuristic method.

TABLE OF CONTENT

DECLARATION

TITLE PAGE

ACKNOWLEDGEMENTS **ii**

ABSTRAK **iii**

ABSTRACT **iv**

TABLE OF CONTENT **v**

LIST OF TABLES **ix**

LIST OF FIGURES **xi**

LIST OF SYMBOLS **xiv**

LIST OF ABBREVIATIONS **xv**

CHAPTER 1 INTRODUCTION **1**

1.1 Research Background 1

1.2 Problem Statement 5

1.3 Aim and Objectives 6

1.4 Research Scope 7

1.5 Thesis Organisation 8

CHAPTER 2 LITERATURE REVIEW **9**

2.1 Introduction 9

2.2 Forming of Boron Steel 9

2.3 Hot Stamping Process 12

2.3.1 Sheet Metal Forming 13

2.3.2	Heating Method	15
2.3.3	Heat Transfer Mechanism	17
2.4	Operation in Hot Stamping	21
2.4.1	Forming process	22
2.4.2	Punching	24
2.5	Hot Stamping Die	26
2.5.1	Die Design	26
2.5.2	Tool Construction	26
2.5.3	Cooling channel system	27
2.5.4	Type of cooling channel	29
2.6	Die Design Optimization	30
2.6.1	Heuristic Method	30
2.6.2	Taguchi Method	32
2.7	Summary	33
CHAPTER 3 METHODOLOGY		35
3.1	Introduction	35
3.2	Material and Sample Preparations	35
3.2.1	Flat Samples	37
3.2.2	U-shape samples	38
3.2.3	U-shape die	40
3.3	Cooling Channel Design for Hot Stamping Tool	41
3.4	Finite Element Analysis	45
3.4.1	Material Data	47
3.4.2	Geometric Modelling	47
3.4.3	Define Constraints	48

3.4.4	Meshing	49
3.4.5	Thermal and Static Analysis	51
3.5	Cooling Channel Design Analysis	54
3.5.1	Heuristic Method	55
3.5.2	Taguchi Method	56
3.6	Hot stamping of 22MnB5 steel	58
3.6.1	Flow rate experimental	59
3.6.2	Heat transfer experiment	60
3.6.3	Tensile Test Measurement by Universal Tensile Machine	64
3.6.4	Hardness Measurement by Vickers Microhardness Machine	64
3.7	Summary	65
CHAPTER 4 RESULTS AND DISCUSSION		66
4.1	Introduction	66
4.2	Finite Element Analysis	66
4.2.1	Meshing	66
4.2.2	Thermal and Static Analysis for flat and U-shaped	69
4.3	Design Optimization	72
4.3.1	Heuristic Method for Flat Sample	72
4.3.2	Heuristic Method for U-Shape Sample	77
4.3.3	Taguchi Method	83
4.3.4	Heuristic and Taguchi Method Comparison	86
4.4	Experiment Validation of Hot Stamped 22MnB5 Steel	88
4.4.1	Validation of FEA Thermal Analysis with Experiment for Flat Tool	88
4.4.2	Validation of FEA Thermal Analysis with Experiment for U-shaped tool	88

4.4.3	Experimental Analysis of Hot Stamping for Flat shaped tool	89
4.4.4	Experimental Analysis of Hot Stamping for U-shaped tool	93
4.5	Summary	94
CHAPTER 5 CONCLUSION		96
5.1	Conclusion	96
5.2	Recommendations	98
REFERENCES		99
APPENDIX A1 G-CODE FOR CUTTING Flat Samples		105
APPENDIX A2 CALCULATION FOR HEAT TRANSFER COEFFICIENT		106
APPENDIX A3 CALCULATION OF HEAT TRANSFER RATE FOR SIMULATION 5 U-SHAPE LOWER TOOL		107
APPENDIX B1 INTERNATIONAL MANUFACTURING ENGINEERING CONFERENCE, ADVANCED MATERIALS RESEARCH VOL. 903 (2014) PP 163-168		108
APPENDIX B2 ADVANCES IN MATERIALS AND PROCESSING TECHNOLOGIES, 2015 VOL. 1, NOS. 1–2, 27–35		109
APPENDIX B3 JOINT CONFERENCE iMEC & APCOMS 2015		110

LIST OF TABLES

Table 1.1	Mechanical and thermal properties of high strength steels	3
Table 2.1	Chemical composition based on weight percentage of boron steel and mechanical properties of boron steel before and after quenching	10
Table 2.2	Temperature dependent properties of boron steel	11
Table 2.3	Value of contact pressure and HTC Standard deviation	20
Table 2.4	Conditions of warm and hot punching process	25
Table 3.1	Mechanical properties of 22MnB5 and SKD61 steel at room temperature	37
Table 3.2	Comparison on blank diameter, stroke of punch (SOP) and schematic diagram of U-shape samples used in previous works and current study	39
Table 3.3	Boundary condition for analysis	49
Table 3.4	Heuristic approach for cooling channel parameter for flat and U-shape	55
Table 3.5	Factor and Level Description for flat shape cooling channel parameter	57
Table 3.6	L9 Test matrix for Flat shape cooling channel parameters	57
Table 3.7	Mechanical Press, OCP 80 specification	58
Table 3.8	Mini Hydraulis Press machine specification	58
Table 3.9	Water flow rate for hot stamping process experiment	59
Table 3.10	Factor and level description of hot stamping process for Taguchi method	60
Table 3.11	L9 Test Matrix hot stamping process for flat shape	61
Table 3.12	Universal Tensile Machine Specification	64
Table 3.13	Wilson Vickers 402 MVD specifications	65
Table 4.1	Meshing results for coarse, medium and fine meshing for flat tool	67
Table 4.2	Meshing results for coarse, medium and fine meshing for U-shape tool	68
Table 4.3	Cooling channel design performance for parameter (C_A) for flat tool	73
Table 4.4	Cooling channel design performance for parameter (C_B) for flat tool	73
Table 4.5	Cooling channel design performance for parameter (C_C) for flat tool	74
Table 4.6	Optimum cooling channel design for flat tool	75

Table 4.7	Effect of cooling channel diameter (C_A) on heat transfer rate and von Mises stress	78
Table 4.8	Effect of pitch between cooling channels (C_B) heat transfer rate and von Mises stress	78
Table 4.9	Effect of distance between cooling channel to tool surfaces (C_C) heat transfer rate and von Mises stress	79
Table 4.10	Effect of the distance cooling channels to wall tool (C_D) heat transfer rate and von Mises stress	80
Table 4.11	Optimum cooling channel design for U-shape tool	80
Table 4.12	Result of Cooling rate and VMS from the Taguchi method for flat tool	83
Table 4.13	Average main effect for cooling rate and VMS for taguchi method of flat tool.	84
Table 4.14	Respond value and S/N ratio for flat tool	86
Table 4.15	Value of tensile strength and hardness	90
Table 4.16	Average main effect for tensile strength and hardness	90
Table 4.17	S/N ratio analysis	92
Table 4.18	Result of responding value from Taguchi method for flat tool experiment	93
Table 4.19	Summarise result tensile strength and hardness for U-shape	94

LIST OF FIGURES

Figure 1.1	The elongation versus strength of different steel material	2
Figure 1.2	Hot stamped parts in typical middle class car	2
Figure 1.3	Mechanical properties of 22MnB5 as delivery and hot stamped	3
Figure 1.4	Basic Hot Stamping process chain	4
Figure 2.1	Temperature, time and transformation diagram of boron steel at different cooling rate	11
Figure 2.2	Direct method of hot stamping	12
Figure 2.3	Indirect method hot stamping	13
Figure 2.4	V-bending operation	14
Figure 2.5	L-Bending process	14
Figure 2.6	U-Bending Process	15
Figure 2.7	Types of heating system (a) Roller hearth furnace, (b) Induction heating and (c) Resistance heating	16
Figure 2.8	Temperature distribution on punching load as a function heating temperature at shearing zone	17
Figure 2.9	Thermal contact resistance with (a) ideal (perfect) thermal contact, and (b) actual (imperfect) thermal contact	18
Figure 2.10	Heat transfer coefficient experiment apparatus	19
Figure 2.11	Heat transfer coefficient as a function of the contact pressure for different tool temperatures	20
Figure 2.12	Typical Forming Limit Diagram	22
Figure 2.13	Sample B-Pillar with tools	23
Figure 2.14	Geometries of die and test piece for (a) V-bending and, (b) U-shape	23
Figure 2.15	Relationship between amount of springback after V-bending and temperature of bending zone (a) relationship between amount of springback high-strength steel after V-bending and temperature of flange (b)	24
Figure 2.16	Warm and hot punching process of UHSS sheet using resistance heating	25
Figure 2.17	Relationship between maximum punching load and heating temperature	25
Figure 2.18	Tool design for the hot stamping process	28
Figure 2.19	Schematic exposition of the quenching tool with integrated heating cartridges	28
Figure 2.20	Schematic of a test hot stamping tool	28
Figure 2.21	The constraints for optimizing cooling channel	29

Figure 2.22	Cooling channel configuration (a) parallel cooling channel, and (b) serial cooling channel	30
Figure 2.23	Experiment steps for Heuristic method	31
Figure 3.1	Research project flow chart	36
Figure 3.2	Flat sample, E8M04	37
Figure 3.3	Process flow for flat sample fabrication	38
Figure 3.4	Process flow for U-shape samples fabrication	39
Figure 3.5	Die design during compression	41
Figure 3.6	U-shape die design	41
Figure 3.7	Hot stamping flat shape tool design	42
Figure 3.8	Hot stamping U-shape shape tool design	43
Figure 3.9	Flat hot stamping tool with cooling channel parameter	44
Figure 3.10	U-shape hot stamping tool with cooling channel parameter	44
Figure 3.11	Flow chart of meshing in FEA of hot stamping	46
Figure 3.12	Toolbox of geometric modelling in ANSYS simulation software	47
Figure 3.13	Flat hot stamping tool import on Ansys software	48
Figure 3.14	U-shape hot stamping tool import on Ansys software	48
Figure 3.15	Thermal contact conductance between blank and die	50
Figure 3.16	Setting interface of thermal and static analysis	51
Figure 3.17	Thermal distribution in the hot stamping tool, (a) heat transfer distribution along 10 s, (b) close-up scale for heat transfer distribution	53
Figure 3.18	Sequence for cooling channel design analysis	54
Figure 3.19	Cooling channel optimization steps using Heuristic method	56
Figure 3.20	Schematic of experimental setup for hot stamping tool	61
Figure 3.21	Hot stamping process flow for (a) Flat shape; (b) U-shape sample	62
Figure 3.22	Thermocouple location for (a) flat shaped tool, (b) u-shaped tool	63
Figure 4.1	Flat shape tool meshing structure at (a) Coarse; (b) Medium and (c) Fine, mesh size at FEA simulation	67
Figure 4.2	U-shaped tool meshing structure at (a) Coarse; (b) Medium and (c) Fine, mesh size at FEA simulation	68
Figure 4.3	Local meshing control for hot stamping tool (a) Mapped mesh (b) Mesh quality criteria chart of mapped mesh.	69
Figure 4.4	Local meshing control for hot stamping tool (a) Refined mesh (b) Mesh quality criteria chart of refined mesh.	69

Figure 4.5	Steady state condition for hot stamping simulation of a) flat sample, b) U-shape sample	70
Figure 4.6	Transient thermal with 10 s quenching time for hot stamping simulation a) flat sample, b) U-shape sample	71
Figure 4.7	Von Mises stress distribution based on static stress analysis on; (a) flat tool, (b) upper U-shape tool and (c) lower U-shape tool	72
Figure 4.8	Flat tool design with optimum cooling channel parameter	75
Figure 4.9	Blank and Tool Condition of flat tool of thermal distribution for holding time for flat tool at (a) 0 s, (b) 4 s, (c) 8 s and (d) 10 s	77
Figure 4.10	U-shape tool design with optimum cooling channel parameter	81
Figure 4.11	Blank and Tool Condition of U-shape tool of thermal distribution for holding time for flat tool at (a) 0 s, (b) 4 s, (c) 8 s and (d) 10 s	82
Figure 4.12	Main effect plot for heat transfer rate of flat tool (a) Diameter of cooling channel (b) Pitch between cooling channel (c) Cooling channel distance to tool surface.	84
Figure 4.13	Main effect plot for maximum von Mises stress (VMS) of flat tool (a) Diameter of cooling channel (b) Pitch between cooling channel (c) Cooling channel distance to tool surface.	85
Figure 4.14	Temperature distribution for cooling channel design of flat tool between heuristic and taguchi method	87
Figure 4.15	Cooling channel design performance for flat shape tool based on heuristic versus taguchi method.	87
Figure 4.16	Comparison of heat transfer distribution between FEA and experiment for flat tool	88
Figure 4.17	Comparison of heat transfer distribution between FEA and experiment for U-shape tool	89
Figure 4.18	Main effects plot for tensile strength of flat tool (a) thickness (b) temperature (c) heating time	91
Figure 4.19	Main effects plot for hardness of flat tool (a) thickness (b) temperature (c) heating time	92
Figure 4.20	Locations on stamped sample for tensile specimen and hardness test	94

LIST OF SYMBOLS

MPa	Mega Pascal
°C/s	Degree Celsius per Second
min	Minutes
s	Second
W/m.K	Watt per Meter Kelvin
mm	Milimeter
°C	Celsius
E	Elastic of Modulus
k	Thermal Conductivity
C_p	Specific Heat
%	Percentage
t	Thickness
B	Bending Length
P	Force
L	Length
Re	Reynolds Number
ρ	Density
μ	Absolute viscosity
V	Velocity
D	Distance
q	heat transfer
h	Heat Transfer Coefficient
A	Heat Transfer Area
T_f	Surrounding fluid temperature
T_s	Surface temperature

LIST OF ABBREVIATIONS

UHSS	Ultra-High Strength Steel
HSS	High Strength Steel
AHSS	Advance High Strength Steel
FEA	Finite Element Analysis
C_A	Diameter of Cooling Channel
C_B	Pitch Between Cooling Channel
C_C	Distance Cooling Channel To Tool Surface
C_D	Distance Cooling Channel To Wall Tool
HTC	Heat Transfer Coefficient
FLD	Forming Limit Diagram
DOE	Design of Experiment
VMS	Von Mises Stress
OA	Orthogonal Array

REFERENCES

- Abdul Hay, B., Bourouga, B., & Dessain, C. (2010). Thermal contact resistance estimation at the blank/tool interface: experimental approach to simulate the blank cooling during the hot stamping process. *International Journal of Material Forming*, 3(3), 147–163.
- Altan, T., & Tekkaya, A. E. (2012). Sheet Metal Forming Process and Application. *ASM International*, 133–156.
- ANSYS. (2016). ANSYS Meshing. Retrieved from <http://www.ansys.com/products/platform/ansys-meshing>
- Assab. (2008). Supreme Hot Work Tool Steel Catalogue. (4th Edition) *Assab Group*.
- Banabic, D. (2010). Sheet Metal Forming Processes. *Springer*.
- Bar-Meir, G. (2009). Fundamental of Die Casting Design. *Springer*
- Barr, R. S., Golden, B. L., Kelly, J. P., Resende, M. G., & Stewart JR, W. R. (1995). Designing and Reproting on Computational Experiment with Heuristic Methods. *Journal of Heuristics*, 9–32.
- Boljanovic, V., & Paquin, J. (2006). *Die Design Fundamental* (3rd Edition) *Industrial Press Inc.*
- Bosetti, P., Bruschi, S., Stoehr, T., Lechler, J., & Merklein, M. (2010). Interlaboratory comparison for heat transfer coefficient identification in hot stamping of high strength steels. *International Journal of Material Forming*, 3(S1), 817–820.
- Çakıroğlu, R., & Acir, A. (2013). Optimization of cutting parameters on drill bit temperature in drilling by Taguchi method. *Measurement*, 46(9), 3525–3531.
- Canakci, A., Erdemir, F., Varol, T., & Patir, A. (2013). Determining the effect of process parameters on particle size in mechanical milling using the Taguchi method: Measurement and analysis. *Measurement*, 46(9), 3532–3540.
- Cengal, Y. A., & Ghajar, A. J. (2011). Heat and Mass Transfer. In *Fundamental and Application (McGraw-Hill)* (p. 9–16, 25–28, 423–426, 488, 489).
- Chang, Y., Meng, Z. H., Ying, L., Li, X. D., Ma, N., & Hu, P. (2011). Influence of hot press forming techniques on properties of vehicle high strength steels. *Journal of Iron and Steel Research International*, 18(5), 59–63.
- Coy, S. P., Golden, B. L., Runger, G. C., & Wasil, E. (2001). Using experimental design to find effective parameter settings for heuristics. *Journal of Heuristics*, 7(1), 77–97.

- Cui, J., Sun, G., Xu, J., Huang, X., & Li, G. (2015). A method to evaluate the formability of high-strength steel in hot stamping. *Materials & Design*, 77, 95–109.
- Dhillon. (2002). Engineering Maintenance A Modern Approach. *CRC Press*.
- Díaz, J., Rusu, C., & Collazos, C. A. (2016). Experimental Validation of a Set of Cultural-Oriented Usability Heuristics: e-Commerce Websites Evaluation. *Computer Standards & Interfaces*, 50(October 2016), 160–178.
- Duncan, J., & Panton, S. (1997). Introduction to sheet metal forming. *Composite Materials Series*, (33), 1–25.
- George, R., Bardelcik, A., & Worswick, M. J. (2012). Hot forming of boron steels using heated and cooled tooling for tailored properties. *Journal of Materials Processing Technology*, 212(11), 2386–2399.
- Hafizuddin. (2014). Dies design structure & manufacturing concept. *Proton Workshop*
- Hoffmann, H., So, H., & Steinbeiss, H. (2007). Design of Hot Stamping Tools with Cooling System. *CIRP Annals - Manufacturing Technology*, 56(1), 269–272.
- Holman, J. (2009). Heat Transfer. *McGraw-Hill*. Retrieved from <http://www.ncbi.nlm.nih.gov/pubmed/21128847>
- Hu, J., Marciniak, Z., & Duncan, J. (2002). Mechanics of Sheet Metal Forming (2nd ed.). *Butterworth-Heinemann*.
- Hu, P., Ma, N., Liu, L., & Zhu, Y. (2013). Theories, Methods and Numerical Technology of Sheet Metal Cold and Hot Forming. *London: Springer London*.
- Hu, P., & Ying, L. (2017). Hot Stamping Advanced Manufacturing Technology of Lightweight Car Body. *Springer London*.
- IISI. (2009). AHSS guideline v4.1. Retrieved from www.worldautosteels.org
- Incropera, F., Dewitt, D., Bergman, T., & Lavine, A. (2002). *Fundamentals of Heat and Mass Transfer*. *John Wiley and Sons Ltd*.
- Iron, I., & Institute, S. (2002). Ultra-Light Steel Autobody Advanced Vehicle Concepts (ULSAB-AVC). *Internal Iron and Steel Institute*.
- Jiang, C., Shan, Z., Zhuang, B., Zhang, M., & Xu, Y. (2012). Hot stamping die design for vehicle door beams using ultra-high strength steel. *International Journal of Precision Engineering and Manufacturing*, 13(7), 1101–1106.
- Karbasian, H., & Tekkaya, a. E. (2010). A review on hot stamping. *Journal of Materials Processing Technology*, 210(15), 2103–2118.

- Kim, H., Kimchi, M., & Altan, T. (2009). Control of Springback in Bending and Flanging Advanced High Strength Steels (AHSS). *International Automotive Body Congress (IABC)*, 1–18.
- Kolleck, R., Veit, R., Merklein, M., Lechler, J., & Geiger, M. (2009). Investigation on induction heating for hot stamping of boron alloyed steels. *CIRP Annals - Manufacturing Technology*, 58, 275–278.
- Kumar, D. D., Shirsat, V., Sharma, V., & Sarpate, C. (2011). Design Optimization of Hot Forming Tools by Numerical Thermal Analysis. *KLT Automotive and Tubular Product LTD*.
- Kumar, P., & Visavale, G. (2013). Grid Generation for Cfd Simulation: Insights With Demo. Retrieved from <http://www.learncax.com/blog/2013/03/22/grid-generation-for-cfd-simulation-insights-with-demo/>
- Lee, M., Kim, S., Nam, H., & Chang, W. (2009). Application of hot press forming process to manufacture an automotive part and its finite element analysis considering phase transformation plasticity. *International Journal of Mechanical Sciences*, 51(11–12), 888–898.
- Lempco. (2000). Die Set Engineering Handbook and Catalog. *Lempco Group*.
- Lempco. (2004). Die Set Engineering Handbook and Catalog. *Lempco Group*.
- Lim, S. K., Azmi, W. H., & Yusoff, A. R. (2016). Investigation of thermal conductivity and viscosity of Al₂O₃/water – ethylene glycol mixture nanocoolant for cooling channel of hot-press forming die application. *International Communications in Heat and Mass Transfer*, 78, 182–189.
- Lim, W. S., Choi, H. S., Ahn, S. Y., & Kim, B. M. (2014). Cooling channel design of hot stamping tools for uniform high-strength components in hot stamping process. *International Journal of Advanced Manufacturing Technology*, 70(5–8), 1189–1203.
- Lin, T., Song, H., Zhang, S., Cheng, M., & Liu, W. (2014). Cooling Systems Design in Hot Stamping Tools by a Thermal-Fluid-Mechanical Coupled Approach. *Advances in Mechanical Engineering*, 2, 1–13.
- Liu, H., Lei, C., & Xing, Z. (2013). Cooling system of hot stamping of quenchable steel BR1500HS: optimization and manufacturing methods. *The International Journal of Advanced Manufacturing Technology*, 69(1–4), 211–223.
- López-Chipresa, E., Mejía, I., Maldonado, C., Bedolla-Jacuindea, A., El-Wahabib, M., & Cabrera, J. M. (2008). Hot Flow Behavior of Boron Microalloyed Steels. *Material Science and Engineering: A*, 480(1–2), 49–55.
- Lundström, E. (2012). Schuler Academy. *Proton Training*.

- Lv, M., Gu, Z., Li, X., & Xu, H. (2016). Optimal Design for Cooling System of Hot Stamping Dies. *ISIJ International*, 1–9.
- Maeno, T., Mori, K., & Nagai, T. (2014). CIRP Annals - Manufacturing Technology Improvement in formability by control of temperature in hot stamping of ultra-high strength steel parts. *CIRP Annals - Manufacturing Technology*, 63(1), 301–304.
- Martí, R., & Reinelt, G. (2011). The Linear Ordering Problem, Exact and Heuristic Methods in Combinatorial Optimization (Vol. 175, pp. 17–41). Berlin, Heidelberg: Springer Berlin Heidelberg.
- Melissa, B. (2012). Fluid Flow Rates. Retrieved from <http://www.education.com/science-fair/article/fluid-flow-rates/>
- Merklein, M., & Lechler, J. (2006). Characterisation of the Flow Properties of the Quenchenable Ultra High Strength Steel 22MnB5. *CIRP Annals - Manufacturing Technology*, 55(1).
- Merklein, M., & Lechler, J. (2008). Determination of Material and Process Characteristics for Hot Stamping Processes of Quenchenable Ultra High Strength Steels with Respect to a FE-based Process Design, *International Journal Material Manufacturing*. 1(1), 411–426.
- Misumi. (2015). Misumi Press Stock Booklet 2015. Retrieved from <http://www.misumi-techcentral.com/tt/en/press/2012/06/126-press-forming-force-3-bending-force.html>
- Mori, K., Maeno, T., & Maruo, Y. (2012). Punching of small hole of die-quenched steel sheets using local resistance heating. *CIRP Annals - Manufacturing Technology*, 61(1), 255–258.
- Mori, K., Maki, S., & Tanaka, Y. (2005). Warm and Hot Stamping of Ultra High Tensile Strength Steel Sheets Using Resistance Heating. *CIRP Annals - Manufacturing Technology*, 54(1), 209–212.
- Mori, K., Saito, S., & Maki, S. (2008). Warm and hot punching of ultra high strength steel sheet. *CIRP Annals - Manufacturing Technology*, 57, 321–324.
- Naderi, M. (2007). *Hot Stamping of Ultra High Strength Steels*.
- Naderi, M., Ketabchi, M., Abbasi, M., & Bleck, W. (2011). Analysis of microstructure and mechanical properties of different high strength carbon steels after hot stamping. *Journal of Materials Processing Technology*, 211(6), 1117–1125.
- Naganathan, A. (2010). *Hot Stamping of Manganese Boron Steel*.
- Naganathan, A., & Penter, L. (2012). Hot Stamping. In *Sheet Metal Forming-Processes and Applications* (pp. 133–156).

- Namklang, P., & Uthaisangsuk, V. (2016). Description of microstructures and mechanical properties of boron alloy steel in hot stamping process. *Journal of Manufacturing Processes*, 21, 87–100.
- Pitts, D., & Sissom, L. (1998). *Schaum's outline of theory and problems of heat transfer. 2nd Edition. McGraw-Hill.*
- PME. (2004). Mould and Die Standards Components. Retrieved from <http://www.docfoc.com/pme-mould-die-standard-components-pdf>
- Roy, R. . (2001). Design of Experiments Using The Taguchi Approach. USA: John Wiley.
- Seok, H., & Koc, M. (2008). Numerical investigations on springback characteristics of aluminum sheet metal alloys in warm forming conditions. *Journal of Material Processing Technology* 204, 370–383.
- Sever, N. K., Mete, O. H., Demiralp, Y., Choi, C., & Altan, T. (2012). Springback Prediction in Bending of AHSS-DP 780. In *NAMRI/SME* (Vol. 40).
- Shahrom, M. S., Yusoff, A. R., & Lajis, M. A. (2013). Taguchi Method Approach for Recycling Chip Waste from Machining Aluminum (AA6061) Using Hot Press Forging Process. *Advanced Materials Research*, 845, 637–641.
- Shapiro, A. (2009). Finite element modeling of hot stamping. *Steel Research International*.
- Skrikerud, M., Megahed, M., & Porzner, H. (2010). Simulation of Hot Stamping Process.
- So, H., Faßmann, D., Hoffmann, H., Golle, R., & Schaper, M. (2012). An investigation of the blanking process of the quenchable boron alloyed steel 22MnB5 before and after hot stamping process. *Journal of Materials Processing Technology*, 212(2), 437–449.
- SositarMold. (2011). Cooling Channel Configuration. Retrieved from <http://www.moldchina.org/cooling-channel-configuration.html>
- Srithananan, P., Kaewtatip, P., & Uthaisangsuk, V. (2016). Micromechanics-based modeling of stress-strain and fracture behavior of heat-treated boron steels for hot stamping process. *Materials Science and Engineering A*, 667, 61–76.
- Steinbeiss, H., So, H., Michelitsch, T., & Hoffmann, H. (2007). Method for optimizing the cooling design of hot stamping tools. *Production Engineering*, 1(2), 149–155.
- Thanadngarn, C., Sirivedin, K., Engineering, M., Thai-german, T. S. I., Buakaew, V., Neamsup, Y., ... Limited, C. (2013). The Study of the Springback Effect in the UHSS by U-bending Process, 6, 19–25.

- Tondini, F., Bosetti, P., & Bruschi, S. (2011). Heat transfer in hot stamping of high-strength steel sheets. In *Journal of Engineering Manufacture* (Vol. 225, pp. 1813–1824). Proceedings of the Institution of Mechanical Engineers, Part B.
- Turetta, A. (2008). *Investigation of Thermal, Mechanical and Microstructural Properties of Quenchenable High Strength Steels In Hot Stamping Operations*. Università Degli Studi Di Padova.
- Wang, S., & Lee, P. (2013). Investigation of Die Quench Properties of Hot Stamping. *China Steel Technical Report*, 2(26), 22–31.
- Xiaoda, L., Xiangkui, Z., Ping, H., & Xianghui, Z. (2016). Thermo-mechanical coupled stamping simulation about the forming process of High-Strength Steel sheet. *International Journal of Control and Automation*, 9(1), 93–102.
- Yanagimoto, J., Oyamada, K., & Nakagawa, T. (2005). Springback of High-Strength Steel after Hot and Warm Sheet Formings. *CIRP Annals - Manufacturing Technology*, 54(1), 213–216.
- Yusoff, A. R., Ghazalli, Z., & Che Hussain, H. (2006). Determining Optimum Edm Parameters in Drilling Small Holes By Taguchi Method. In *Proceedings of ICOMAST2006 International Conference on Manufacturing Science and Technology*.
- Zhang, Z., Li, X., Pan, L., & Wei, X. (2010). Numerical Simulation on Hot Forming of B Pillar.
- Zhang, Z., Li, X., Zhao, Y., & Li, X. (2014). Heat transfer in hot stamping of high-strength boron steel sheets. *Metallurgical and Materials Transactions B: Process Metallurgy and Materials Processing Science*, 45(4), 1192–1195.
- Zhong-de, S., Mi-Ian, Z., Chao, J., Ying, X., & Wem-juan, R. (2010). Basic Study On Die Cooling System Of Hot Stamping Process. *International Conference on Advanced Technology of Design and Manufacture*, 67(0 2), 5–8.